

Gull River Affordable Housing project lift station

Item#	Qty	Description
1.1	2	3069.180-0877 FLYGT MODEL DX-3069 SUBMERSIBLE PUMP 2.3HP/1.7KW 230VOLT 1PHASE 60HZ 2POLE HT IMPELLER CODE 253, VOLUTE 2" 16M 4G2.5+2X1.5 FLS
1.2	2	806 99 00 INSTALLATION KIT
1.3	16	13-50 05 27 CALIBRATED CHAIN 9/32" S/S 316 GR 50 COMPATIBLE WITH HOIST 13-43 00 06
1.4	2	13-44 00 58 CHAIN CONNECTOR 9/32 STAINLESS STEEL 316L GRADE 50
1.5	2	13-44 00 61 MASTER LINK 1/2" S/S 316L GRADE 50
1.6	2	83 57 23 SUPPORT GRIP
1.7	1	9412 DUPLEX NEMA 4 X CONTROL PANEL 230/1 COORDINATED MOTOR STARTERS WITH SINGLE PHASE STARTER KITS HOA HI LEVEL ALARM HORN AND GLOBE FAULT LIGHTS HOUR METERS LED INDICATION LIGHTS 4 FLOAT CONTROLS WITH ISR'S MINICAS MONITORING PUMP MONITORING RELAY



Item#	Qty	Description
1.8	4	582 88 13 LEVEL REGULATOR DENSITY: 0.95-1.10, FLOAT COLOR: GREY, BLACK NBR/PVC 20M CABLE
1.9	1	8008 5' DIA x 18' DEEP TOPS Wetwell Tank Base Price Includes: FRP filament wound shell section joined to TOPS basin Sanitary white corrosion liner, 110mil thick Syracuse Aluminum top with Safe Hatch bolted and sealed to the shell flange One cable hanger bolted to access hatch 316 Stainless Steel guide rails Flygt SS guide rail brackets upper and intermediate as needed 1 inlet sleeve laminated to shell with link seal for up to 8" pipe inlet Green gelcoat on top 2' of shell for UV protection All bolting penetrations through shell to be laminated over All piping projections to be 6" beyond Link-Seal sleeves 2" drain connection from vault with PVC flapper check valve when applicable Bulkhead style PVS electrical connections 1-3" & 1-1.25" 1-4" Sched 40 PVC candy cane or mushroom style vent Flygt logo painted onto shell or cover Shipping saddles banded to tank Generic fill in blanks drawing TOPS Wetwell Piping Price in Single or Dual Discharge Includes: All pipe and fittings required in wetwell in PVC or SS HDL check valves in single discharge applications Valmatic plug valves in single discharge applications Union or flanged connection before all forcemain penetrations SS bolting hardware and gaskets for flanged connections SS support angles and hardware for piping and guide rails as needed Flygt discharge connections bolted and sealed to basin Valve Vault Piping Base Price Includes: All pipe and fittings required in vault in SS as per piping size HDL check valves, Valmatic Plug Valves FRP sleeves laminated to shell & link seal for 3 only forcemain penetrations SS bolting hardware and gaskets for flanged connections SS angle and adjustable floor stands for support of piping 2 only dresser #38 or other approved couplers in between Wetwell and Vault 1 - SS restraint coupler after Tee on piping header for ease of valve removal Notes: All pump station and Vaults will bear Barski SS label with stamped date and W.O # All pump station and Vaults have a 5 year all-inclusive warranty Only factory installed electrical couplers to be used on insulated stations No intermediate platform included this is optional For H-20 applications our engineered stations are to be used
1.10	2	13-56 03 11 TEST FAL 2.2 PLOT"D 3045-3127+ FAL 15-906
1.11	1	13-56 03 68



Item#	Qty	Description
		TEST FAL 2.12 ADDL CERT + FAL 15-9018
1.12	1	13-56 00 10 ENGINEERING START UP
1.13	1	13-56 00 24A FREIGHT CHARGES TXBL

